



www.gravure-marseille.com
seals - wax seals - wax
brass relief stamps
brands hot leather and wood




Tips for the realization and transmission of logo files, images, patterns.

The file is downloaded in the "**Product Customization**" section of the article ordered.

For seals intended for the creation of wax seals.

The drawings with shades, azures, guilloches, renderings of volume,



Eg are not feasible. It is the impression in the wax that will give relief. Drawings, patterns, logos with overlapping colors, gradients are to be studied on a



case by case basis, eg: . To evaluate the project, conversion into Black and White gives a good idea of the result.

The scaling of the drawing, pattern or logo will also make it possible to determine the fineness of the lines and the legibility of the result.

The lines in black (which will be engraved in relief and will then emerge in relief in the wax) must have a minimum thickness of 0.35 mm. The distance between two black lines must be at least 0.30 mm.

In the case of text to be engraved, and to ensure its proper reading, the height of characters to be used must be 3.00 mm.

You should also use a "Batons" style Arial, Helvetica or similar (ABCDE abcde). It is preferable not to use the English typeface (*ABCDE abcde*) for small characters.

You can address your files in formats

Picture :

Psd, bmp, jpg, tif, png, ...

Vectorized (preferred file type for the correct reproduction of the project):

Eps, ai, svg, plt, hpg,

Mixed:

The .pdf format is also a good means of transmission.

If a file is not received successfully or if the file is corrupted, we will contact you to find the best solution.